SECTION 3400: PAVEMENT LAYERS OF GRAVEL MATERIAL

B3402 MATERIALS

(a) General

In Table 3402/1 under the "G5" column delete the words "may contain approved natural fines not obtained from parent rock "in the "Additional Fines" row and replace it with the following:

"May contain up to 15% by mass of approved natural fines (or sand) not necessarily obtained from parentrock. Added fines shall have a LL not exceeding 25 and PI not exceeding 6."

Revise the relevant portion of Table 3402/5 as follows:

Table B 3402/5 : Requirements for Chemically Stabilized Pavement Layers

CRITERIA	C3	C4
Durability : Fines lost Wet-dry	20% maximum	30% maximum

b) Compaction requirements

Amend the compaction requirements by changing all references to "modified AASHTO density", to "Maximum Dry Density (MDD)" as follows:

- "Lower selected layer: 93% of MDD
- Upper selected layer: 95% of MDD
- Subbase: 97% of MDD
- Shoulder & wearing course: 95% of MDD"

B3406 QUALITY OF MATERIALS AND WORKMANSHIP

Amend the second paragraph of this clause to read as follows:

"Level and thickness tolerances shall be in accordance with the provisions of Section 8200: Judgement Plan A and density test results for gravel base will be assessed in accordance with the provisions of Section 8200: Judgement Plan B. All other test results shall comply fully with the specified requirements and limit values."